

## BaseLine

### Desktop telephone

#### Key features

- Easy to use
- Message waiting lamp
- Hold key
- 13 memories
- 3 direct memories
- Adjustable ringing tone
- Adjustable ringing volume
- Last number redial
- Mute in handset
- Ringer LED
- Save key



The BaseLine analogue telephone is designed for the business user. The set is more robust than a regular consumer set.

The BaseLine is optimised for the business users' environment.

Complementary to the extensive features that may be expected from luxury analogue telephone sets, the BaseLine offers PBX-specific functionality.

Transfer facilities are supported by a special yellow Hold key.

A Message Waiting Lamp facilitates the use of Voicemail.

**NEC PHILIPS**

NEC PHILIPS UNIFIED SOLUTIONS

## User benefits

- Voicemail is efficiently supported by the message-waiting lamp
- The yellow Hold key gives access to the transfer facilities of the switch
- 3 direct memories plus 10 phonebook memories for storing frequently used numbers
- Last Number Redial facilitates quick redialling
- The Save key allows temporary storage of a number
- Ringing tone selection allows distinguishing ringing phones in one room
- Mute enables you to consult a colleague, without the caller overhearing

## Features

BaseLine features	
Called number display	-
Calling number display	-
Check key for memory	-
Direct memories	3
Earth recall	√
Hands-free	-
Indirect memories	10
Last Number Redial	√
Line Power	√
Listen-in	-
Memory back-up	√
Message Waiting LED	√
Mute	√
Pause insertion	√
Post dialling DTMF	√
Pulse dialling	-
Receiver volume control	-
Ringing tone selection	√
Ringing volume control	√
Ringer LED	√
Save key (for temporary storing)	√
Speaker volume control	-
Tone dialling	√
Time-break recall	√
Timer key	-
Time & call duration	-
Wall Mounting	√

## Technical data

### Physical characteristics

- Size: 160 × 205 × 62 mm (w × d × h)
- Weight: 675 g
- Colour: dark grey/charcoal

### Packaging

- Box size: 215 × 237 × 58 mm (w × d × h)

### Environmental conditions

- Temperature range:
  - rated -5° C to +45° C
  - transport -15° C to +55° C
- Relative humidity:
  - non condensing
  - rated 10% to 90% RH
  - transport 5% to 95% RH

### Operating conditions

- The BaseLine is line powered
- Up to 3 sets can be connected to one PBX port. This is reduced to 1 if message waiting is enabled on the set
- Two types of message waiting indication are supported.
  - polarity reversal, activation voltage 20..60V, deactivation <2V
  - high voltage, activation voltage 85..120V, deactivation <65V
- Transmission settings and voice quality are in compliance with the European telecom requirement TBR38

### Compatibility

- Operation is successfully verified on the iS3000, 2000 IPS, SV7000, IPC 100 and IPC 500 communication platforms

### Compliance

- European Directives: Safety: 2006/95/EC / EMC: 89/336/EEC / R&TTE: 1999/5/EC / RoHS: 2002/95/EC / WEEE: 2002/96/EC
- Council Recommendation: EMF 1999/519/EC
- European Standards: EN55022: 2006 Class B / EN55024: 1998+A1: 2001+A2: 2003 / EN60950-1: 2001+A11: 2004 / EN50371: 2002
- Telecom: TBR21: 1998 / TBR38: 1998

### Deliverables

- The BaseLine sets are supplied with:
- a line cord (3 m long with RJ11 plugs on both ends)
  - a multilingual user guide (Danish, Dutch, English, French, German, Italian, Portuguese, Spanish, and Swedish)
  - a wall mounting bracket

For further information please contact your local NEC Philips office or:

**NEC Philips Unified Solutions**  
P.O. Box 32  
1200 JD Hilversum  
The Netherlands  
Phone: +31 35 689 91 11  
Fax: +31 35 689 14 50  
www.nec-philips.com